

GUND (Geoid Undulation) =
The height of the Geoid (MSL) above the
Reference Ellipsoid (WGS 84) at the stated position.

BEARINGS ARE MAGNETIC
ELEVATIONS AND HEIGHTS ARE IN FEET

ELEVATIONS IN FEET AMSL
HEIGHTS IN FEET ABOVE AD

38
(21)

0100200300500

0100200300500

500100200300500

500100200300500

RUNWAY/TAXIWAY/APRON PHYSICAL CHARACTERISTICS			
APRON / RWY / TWY	SURFACE	BEARING STRENGTH	ELEVATION
RWY 27	Grooved Asphalt	30F/C/Y/T	14ft amsl
RWY 09	Grooved Asphalt	30F/C/Y/T	17ft amsl
Main Apron	Macadam	27F/C/Y/T	-
Western Apron	Macadam	23F/C/Y/T	-
Taxiway A	Macadam	23F/C/Y/T	-
Taxiway B	Macadam	16F/C/Y/T	-
Taxiway C	Macadam	-	-
Taxiways D & E	Macadam	12F/C/Y/T	-



COM		DUNDEE INFORMATION	
ATIS	119.330	DUNDEE TOWER	
TWR	122.905	DUNDEE FIRE	
LIGHTING			
APCH 09	HI 375m uni-d with 2 crossbars.		
THR 09	HI elevated green with HI elevated green W bars.		
THR 27	HI elevated green.		
RWY 09/27	HI elevated bi-d with LI omni-d component. White with end 360m yellow caution zone. End lights elevated red.		
TWY	Blue edge on A/B/D/E. Guard Lights at holds A & B.		