

Instrument Approach Procedure Coding Tables

LEEDS EAST RNP RWY 24 - Instrument Approach Procedure via IDDAH

Designator	Sequence Number	Path Terminator	Waypoint Name	Fly-over	Course/Track °M (°T)	Turn Direction	Level Constraint	Speed Constraint	Co-ordinates	Remarks and Distance to MAPt
R24R	001	IF	IDDAH	N	-	-	<u>3000</u>	-185	540044.26N 0005807.98W	IAF
R24R	002	TF	CM24I	N	180° (180.0°)	RIGHT	<u>2300</u>	-185	535544.80N 0005807.98W	IF / 9.3NM
R24R	003	TF	CM24F	N	235° (234.8°)	-	2000	-	535350.29N 0010242.58W	FAF / 6.0NM
R24R	004	TF	RW24	Y	235° (234.8°)	-	-	-	535021.47N 0011102.25W	MAPt
R24R	005	TF	CMM07	N	235° (234.7°)	RIGHT	-	-170	534726.03N 0011759.97W	-
R24R	006	TF	CMM08	N	325° (324.6°)	RIGHT	-	-170	535111.23N 0012230.88W	-
R24R	007	TF	CMM09	N	055° (054.5°)	RIGHT	<u>2500</u>	-170	535410.47N 0011524.40W	-
R24R	008	TF	CMM10	N	129° (129.0°)	LEFT	<u>3000</u>	-170	534827.95N 0010331.35W	-
R24R	009	TF	VUSFO	N	060° (059.8°)	-	3500	-185	535232.00N 0005138.62W	-

LEEDS EAST RNP RWY 24 - Instrument Approach Procedure via VUSFO

Designator	Sequence Number	Path Terminator	Waypoint Name	Fly-over	Course/Track °M (°T)	Turn Direction	Level Constraint	Speed Constraint	Co-ordinates	Remarks and Distance to MAPt
R24L	001	IF	VUSFO	N	-	-	<u>3500</u>	-185	535232.00N 0005138.62W	IAF
R24L	002	TF	CM24I	N	310° (310.0°)	LEFT	<u>2300</u>	-185	535544.80N 0005807.98W	IF / 9.3NM
R24L	003	TF	CM24F	N	235° (234.8°)	-	2000	-	535350.29N 0010242.58W	FAF / 6.0NM
R24L	004	TF	RW24	Y	235° (234.8°)	-	-	-	535021.47N 0011102.25W	MAPt
R24L	005	TF	CMM07	N	235° (234.7°)	RIGHT	-	-170	534726.03N 0011759.97W	-
R24L	006	TF	CMM08	N	325° (324.6°)	RIGHT	-	-170	535111.23N 0012230.88W	-
R24L	007	TF	CMM09	N	055° (054.5°)	RIGHT	<u>2500</u>	-170	535410.47N 0011524.40W	-
R24L	008	TF	CMM10	N	129° (129.0°)	LEFT	<u>3000</u>	-170	534827.95N 0010331.35W	-
R24L	009	TF	VUSFO	N	060° (059.8°)	-	3500	-185	535232.00N 0005138.62W	-