

Instrument Approach Procedure Coding Tables

Manchester RNP RWY 23L - Instrument Approach Procedure via TINVA

Designator	Sequence Number	Path Terminator	Waypoint Name	Fly-over	Course/Track °M (°T)	Turn Direction	Level Constraint	Speed Constraint	Co-ordinates	Remarks and Distance to MAPt
R23LR	001	IF	TINVA	-	-	-	<u>3500</u>	185	533257.59N 0020449.54W	IAF
R23LR	002	TF	C23LI	-	141° (141.1°)	RIGHT	<u>3500</u>	-	532905.02N 0015934.99W	IF / 13.1NM
R23LR	003	TF	C23LF	-	231° (231.3°)	-	2500	-	532515.77N 0020733.36W	FAF / 7.0NM
R23LR	004	TF	RW23L	Y	231° (231.2°)	-	-	-	532053.35N 0021637.94W	MAPt
R23LR	005	CA	-	-	231° (231.1°)	-	3500	-	-	-

Manchester RNP RWY 23L - Instrument Approach Procedure via DOMIG

Designator	Sequence Number	Path Terminator	Waypoint Name	Fly-over	Course/Track °M (°T)	Turn Direction	Level Constraint	Speed Constraint	Co-ordinates	Remarks and Distance to MAPt
R23LC	001	IF	DOMIG	-	-	-	<u>3500</u>	185	533211.72N 0015303.47W	IAF
R23LC	002	TF	C23LI	-	231° (231.4°)	-	<u>3500</u>	-	532905.02N 0015934.99W	IF / 13.1NM
R23LC	003	TF	C23LF	-	231° (231.3°)	-	2500	-	532515.77N 0020733.36W	FAF / 7.0NM
R23LC	004	TF	RW23L	Y	231° (231.2°)	-	-	-	532053.35N 0021637.94W	MAPt
R23LC	005	CA	-	-	231° (231.1°)	-	3500	-	-	-

Manchester RNP RWY 23L - Instrument Approach Procedure via OSNAP

Designator	Sequence Number	Path Terminator	Waypoint Name	Fly-over	Course/Track °M (°T)	Turn Direction	Level Constraint	Speed Constraint	Co-ordinates	Remarks and Distance to MAPt
R23LL	001	IF	OSNAP	-	-	-	<u>3500</u>	185	532512.22N 0015421.40W	IAF
R23LL	002	TF	C23LI	-	321° (321.2°)	LEFT	<u>3500</u>	-	532905.02N 0015934.99W	IF / 13.1NM
R23LL	003	TF	C23LF	-	231° (231.3°)	-	2500	-	532515.77N 0020733.36W	FAF / 7.0NM
R23LL	004	TF	RW23L	Y	231° (231.2°)	-	-	-	532053.35N 0021637.94W	MAPt
R23LL	005	CA	-	-	231° (231.1°)	-	3500	-	-	-